

cPCIS-P2630R

4U CompactPCI Hybrid PlusIO System with
5 CompactPCI and 4 CPCI-S.0 Peripheral Slots



Features

- 3U CompactPCI PlusIO backplane with five CompactPCI and four CPCI-S.0 peripheral slots and one system slot
- Temperature, voltage, and fan monitoring LEDs
- Supports rear I/O backplane with P2 connectors for cPCI 50mm/80mm depth RTMs
- Temperature, voltage, and fan monitoring LEDs
- Hot-swappable cooling fans & filter
- 400 W ATX Power supply

Ordering Information

Model Name	System	Peripheral	Rear	Alarm Module	PSU	Max. Power	PICMG
cPCIS-P2630R	1	5+4	5	Yes	1 ATX	400 W	2.0, 2.1

Note: Models above do not include any system or peripheral boards.

Specifications

CompactPCI Standard	2.0 R3.0, 2.1 R2.0, 2.30, CPCI-S.0
Form Factor	3U 84HP CompactPCI
Enclosure	19" 3U rackmount enclosure
Power Supply	Industrial grade ATX power supply or PICMG 2.11 47-pin 3U CompactPCI power module(s) available on request
Backplane	3U 32-bit 10-slot CompactPCI PlusIO hybrid backplane, other backplane models available on request
Dimensions	482.6 x 177.8 x 258 mm (W x H x D)

cPCIS-3048 Series

3U CompactPCI Enclosure with 6-slot Backplane
and Redundant Power Modules



Features

- 3U CompactPCI backplane with one system slot and five peripheral slots
- Suitable for rackmount applications
- 3U 48HP fanless enclosure
- Optional redundant CompactPCI power modules

Ordering Information

Model Name	Segment	System	Peripheral	Rear	PSU	Max. Power	PICMG
cPCIS-3048	1	1	5	-	1	250 W	2.0, 2.1, 2.11
cPCIS-3048/DP	1	1	5	-	2	500 W	2.0, 2.1, 2.11

Notes: Models above do not include any system or peripheral boards.

Specifications

CompactPCI Standard	2.0 R3.0, 2.1 R2.0
Form Factor	3U 48HP CompactPCI
Enclosure	3U fanless rackmount enclosure
Power Supply	PICMG 2.11 47-pin 3U CompactPCI AC or DC power module(s), dependent on subsystem configuration
Backplane	6-slot 32-bit 3U backplane. Other backplanes available on request.
Dimensions	259.72 x 132.2 x 243.5 mm (W x H x D)